LENSEC LXS6

LENSEC LXS6 Network Video Appliance

Product Datasheet



Introduction

LENSEC LXS6 is an affordable small form factor appliance designed for small deployments running on top of Microsoft Windows 10.

This surveillance-optimized server support up to 16 cameras streaming and recording at high resolution. Cameras and security systems licenses are obtained separately.

LENSEC LXS6 comes pre-downloaded and enhanced with Perspective VMS[®], which eliminate deployment cost and enable instant-use of appliance.

Cost-Effective

LENSEC LXS6 delivers a perfect balance between low budget, storage scalability and performance. This series is the ideal appliance as central management server, remote site NVR and standalone deployments.

LENSEC LXS6 offers up to $1 \times 3.5^{"}$ hard drives with a total storage capacity of 20 TB.

High Performance

LENSEC LXS6 accelerates your network surveillance infrastructure response with improved performance by using Intel i-series processors.

OS/VMS loaded on (1) M.2 SSD sticks for faster booting and higher applications response time. It handles well the system management role with high response to users' requests and third-party security integration services.

Key Features

- Windows[®] 10
- Intel[®] i-Series
- Up to 60 Mbps throughput
- Up to 20 TB SATA drives
- 5 Year, Next-Business Day Warranty

LENSE

LENSEC LXS6



LENSEC LXS6 NVA Technical Specifications

General information

Operating System Microsoft Windows[®] 10

Processor Intel[®] Core[™] i3-12100 3.3 Ghz. 4C/8T

Memory 16 GB (2 x 8 GB)

Power Supplies 180W Power Supply

Networking 1 x 1GbE ports

GPU (Optional) NVIDIA®T400, NVIDIA®T1000

Performance Validated 16 cameras*

Remote Users No license limitation

VMS Edition Support PVMS Express, Standard, Professional, Enterprise

Operation Mode Standalone/Centralized/Distributed

Support and Warranty 5-Year Next-Business Day, Customer self-repair for HDD & GPU

Storage

VMS/OS Disk 1 x 256 GB M.2 SSD

Storage Bays Up to 1 x 3.5"

Storage Capacity Up to 20 TB

Mechanical

Form Factor Small Form Factor

Dimensions Form Factor 3.65" (92.6mm) x 11.53" (292.8mm) x 11.42" (290mm)

Temperature Storage (Min) 41°F - (Max) 95° F [(Min) 5°C - (Max) 35° C]

Humidity Storage 5% to 95% RH Operating: 10% to 80% RH

Maximum Weight 5.02 kg (11.07 lbs)

Storage Configuration

Models	Bays	Max. Storage Capacity
LXS6-20TB	1 x 3.5" SATA	20 ТВ

*Up to 16 Cameras with 1920x1080, 25FPS & 3 Mbps